

### **ABXOLUT AX5-TS**

### Sediment, Scale, Taste and Odour Reduction



Abxolut ONE DESIGN

### Applications:

- Water Heaters
- Household Appliances
- Coffee Makers
- Ice Machines
- Distillers
- Steam Generators

### **Filter Replacement Instructions**

- 1. Shut off the water supply
- 2. Release the water pressure
- 3. Grasp existing filter and remove by rotating left until it stops, then pull down releasing it from the filter head
- 4. Align replacement filter guide channels with the corresponding posts of the filter head
- 5. Insert the filter upward until it fully seats into the head, then rotate right until it stops
- 6. Flush the system for 5 minutes before use



Please send the used filters back to us and we will have them recycle.

# For applications in which water is heated

past its boiling point, it is usually advisable to employ one, if not many scale reduction techniques in water filtration to safeguard against scale build-up in water boilers. Such buildup can lead to machinery damage, and if left unattended, failure.

AX5-TS is a 5 micron scale inhibitor water filter cartridge designed to address these problems. Perfect for use in commercial applications or home with kitchen equipment and coffee and ice machines to prevent scale build up and damage to your machines. It reduces chlorine, taste, odour, sediment and scale control.

### Specification

Flow Rate: 7.5 L/min Capacity: 25,000 litres Micron Rate: 5 Ports (inlet/outlet): 15mm Max. Temperature: 38°C Min. Pressure: 172 kPa Max. Pressure: 860 kPa (non-shock)

### Dimension: 80 mm (dia) x 300 mm (H)

## Quick & easy to replace the cartridge





Turn anti-clockwise and pull downward

Push up and turn clockwise until stop

Xsential Pty Ltd 78 Daly St reet Ascot Western Australia 6104 Ph: 1300 366 295email: sales@xsential.com.au www.xsential.com.au