

Congratulation on your purchase of your WarewasX WX10, the under-sink solution for scale control for your dishwasher. WarewasX WX10 uses a food grade citrus formulation to naturally condition your water for clean dishes load after load for up to 3 months with a single cartridge. WashwasX WX10 is uniquely effective in preventing and removing hard water spotting on your dishes and scale buildup from your dishwasher.



WashwasX WX10 will help reduce the detergent usage significantly for your dishwasher. This help reduce the environmentally foot print and save you money. So please adjust the detergent usage accordingly. Avoid using pre-soaks or rinse aids. Using too much detergent or rinse-aids may cause a fine white film or spots to form on dishes or glasses.

CAUTION– READ THE INSTRUCTION FIRST

The fitting comes with the system has TWO different type of thread. Make sure these thread are screw into the right area. The NPT thread part will need to screw on to the WX10 head. Wrong installation may result in an unusable system.

1. Tape the both NPT brass fitting ends and screw it onto the WX10 head.
2. You may screw the water supply to the BSP thread end of the INLET of WX10 and OUTLET of the WX10 to the dishwasher.

To remove the WX10 cartridge

1. Locate the RED locking pin. The RED locking pin can be located on the front or the back depending on how it was installed.
2. Lift the RED locking pin and rotate the cartridge anti-clockwise while lifting the pin.
3. Pull down the cartridge.

Installing the new cartridge is very easy. Just insert the cartridge and turn clockwise until the RED pin is clicked/ locked.



www.xsential.com.au

DISCLAIMER

WashwasX WX10 water treatment system becomes an integrated component of your dishwasher plumbing system. Hence a regular maintenance is required to ensure the system is working effectively. For maximum efficiency, please do not use the dishwasher immediately after the installation. Allow the new cartridge to remain in the housing with the minimal water flow for one hour. Replace the cartridge if the system remains unused for longer than 60 days. A cartridge should never be left connected to the system for longer than 6 months before replacement. Always disconnect or turn off the water supply line if the system is expected to be idle for longer than 6 months.

Note: A 350kPa water pressure reduction valve must be installed with the filter.

Xsential Pty Ltd
78 Daly Street Ascot
Western Australia 6104
Ph: 1300 366 295 Fax: (08) 9277 2266
email: sales@xsential.com.au